


## RISTRETTO

208107A 48" LED Chandelier

## FINISHES

208107A  
Matte Black

## PRODUCT ATTRIBUTES

|                  |                     |
|------------------|---------------------|
| Fixture Finish   | Matte Black         |
| Fixture Material | Steel, Aluminum     |
| Shade Finish     | Clear Ribbed, White |
| Shade Material   | Acrylic             |
| UPC Code         | 9008606403745       |
| Warranty         | 5 years             |

## DIMENSIONS

|                     |                                                   |
|---------------------|---------------------------------------------------|
| Fixture (W x D x H) | 48" (1219 mm) x 48" (1219 mm) x 36" (916 mm)      |
| Shade (W x D x H)   | 2.25" (55 mm) x 2.25" (55 mm) x 6.25" (156 mm)    |
| Canopy (W x D x H)  | 6.5" (165 mm) x 6.5" (165 mm) x 1.5" (40 mm)      |
| Canopy Shape        | Round                                             |
| Min. Height         | 39.75" (1008 mm)                                  |
| Max. Height         | 93.75" (2380 mm)                                  |
| Wire                | 144" (3660 mm)                                    |
| Rods                | 2 x 3" (76 mm), 2 x 6" (152 mm), 3 x 12" (305 mm) |
| Weight              | 27.78 LBS12.6 KG                                  |

## LIGHT SOURCE

|                       |                      |
|-----------------------|----------------------|
| Light Source          | 72W LED (Integrated) |
| Color Temp. (K)       | 3000K                |
| Initial Lumens (lm)   | 8400                 |
| Delivered Lumens (lm) | 4137                 |
| CRI (Ra)              | >90                  |
| Lifetime Hours        | 50000 (L70)          |
| Dimmable              | Yes                  |
| Dimming Method        | Triac                |

## SPECIFICATIONS

|                    |                          |                  |     |
|--------------------|--------------------------|------------------|-----|
| Input Voltage      | 120-277V, 60Hz           | Output Voltage   | 36V |
| Driver Type        | DC                       |                  |     |
| System Type        | Hardwired                |                  |     |
| Certifications     | cETLus, FCC/ICES 005     |                  |     |
| Location Rating    | Dry                      |                  |     |
| Mounting Direction | Ceiling                  |                  |     |
| Sloped Ceiling     | Yes                      | Max. Slope Angle | 90° |
| Light Direction    | Ambient                  |                  |     |
| Adjustability      | Adjustable Height - Rods |                  |     |