

## RILEY

208579A 31" 5CCT LED Chandelier

## FINISHES



## PRODUCT ATTRIBUTES

|                   |                                      |
|-------------------|--------------------------------------|
| Fixture Finish    | Coffee Faux Leather / Textured Black |
| Fixture Material  | Steel, Aluminum, Faux Leather        |
| Diffuser Finish   | Matte White                          |
| Diffuser Material | Acrylic                              |
| Switch Type       | 5CCT Slide Switch                    |
| UPC Code          | 9008606416141                        |
| Warranty          | 5 Years                              |

## DIMENSIONS

|                     |                                                   |
|---------------------|---------------------------------------------------|
| Fixture (W x D x H) | 31.5" (800 mm) x 31.5" (800 mm) x 11.75" (300 mm) |
| Canopy (W x D x H)  | 9.5" (240 mm) x 9.5" (240 mm) x 1.5" (36 mm)      |
| Canopy Shape        | Round                                             |
| Min. Height         | 15.25" (390 mm)                                   |
| Max. Height         | 144" (3657 mm)                                    |
| Wire                | 144" (3660 mm)                                    |
| Weight              | 11.24 LBS 5.1 KG                                  |

## LIGHT SOURCE

|                       |                                   |
|-----------------------|-----------------------------------|
| Light Source          | 91W LED (Integrated)              |
| Color Temp. (K)       | 2700K, 3000K, 3500K, 4000K, 5000K |
| Initial Lumens (lm)   | 10368                             |
| Delivered Lumens (lm) | 8257                              |
| CRI (Ra)              | >90                               |
| Lifetime Hours        | 50000 (L70)                       |
| Dimmable              | Yes                               |
| Dimming Method        | Triac                             |

## SPECIFICATIONS

|                    |                              |                |     |
|--------------------|------------------------------|----------------|-----|
| Input Voltage      | 120-277V, 50/60Hz            | Output Voltage | 36V |
| Driver Type        | DC                           |                |     |
| System Type        | Hardwired                    |                |     |
| Certifications     | cETLus, FCC/ICES 005         |                |     |
| Location Rating    | Dry                          |                |     |
| Mounting Direction | Ceiling                      |                |     |
| Sloped Ceiling     | No                           |                |     |
| Light Direction    | Ambient                      |                |     |
| Adjustability      | Adjustable Height - Push-Pin |                |     |